

### The New Range of Bohemia X Multifuel Stoves - approved for wood burning use in smoke control areas throughout the UK

Pevex Enterprises has been established for over 17 years and is a successful, specialist distributor and manufacturer of wood and multifuel stoves and fireplaces to the UK retail fireplace industry.

The Bohemia X multifuel stove range featured in this brochure is the latest addition to our portfolio of stoves, British designed to meet the requirements and needs of the typical English traditional and contemporary fireplace settings. Incorporating the latest in clean burn technology and approved for wood burning in smokeless zones throughout all areas of the UK and covering outputs from 3kW to 8kW. The Bohemia X stove range is the second generation of the standard Bohemia range and is a continuation of our development of making a good range even better with higher efficiencies, lower CO and improved engineering with 5mm steel used for the body and 8mm steel for the top plate. All free standing stoves are fitted with adjustable feet and bolt-on flue collars for ease of installation. Bohemia X stoves are better for the environment, have lower fuel consumption and are strongly built for a long and trouble free life and are supported by a **5 year manufacturers guarantee**\*.

The firebox technology incorporated across the range features a Vermiculite lined fire chamber, twin baffle system and injected tertiary air, all designed to make the fire burn brighter and hotter which greatly improves the overall performance available from these stoves. With primary and secondary air sliders the fire in the stove can be controlled whilst the built in air wash keeps the glass clean.

Pevex prides itself on first class customer service and continuous and innovative design solutions to make our range of stoves better, stronger and more efficient to meet todays and tomorrows needs and requirements for our homes and the environment.

Bohemia X stoves are available through all good stockists throughout the UK. Call us now to find out the location of your nearest dealer on 01473 736399 or email sales@pevexenterprises.co.uk



Front cover picture: Bohemia X40 Cube

excluding glass, grate and firebricks.





## 3-4kW Multi Fuel Stove

A delightful compact steel stove that will fit into a small fireplace opening measuring 18" (457mm) x 24" (610mm) and will happily burn wood or smokeless fuel giving a cosy radiant and convected heat from the built in top convector plate whilst giving a lovely view of the fire. Ideal for smaller rooms, cottages or narrow boats. With its clean burn firebox technology the X30 is fully approved for use in smokeless zones throughout all areas of the UK.



Dimensions	: W390 x D290 x H521mm
Weight	: 51kg
Max log length	: 300mm (12")
Flue outlet	: 125mm top/rear
Efficiency wood	: 79.2%
Efficiency smokeless fuel	: 75%



Optional decorative cast iron door available







The Bohemia X40 gives a full size appearance from the front but its shallow depth allows it to be installed into small rooms or town houses where space may be at a premium. Load a 16" log and enjoy the fire burning brightly through the large glass window or burn smokeless fuel and feel the wonderful warm radiant and convected heat that this stove delivers.

Dimensions	: W545 x D292.5 x H606mm
Weight	: 66kg
Max log length	: 400mm (16")
Flue outlet	: 125mm top/rear
Efficiency wood	: 79.5%
Efficiency smokeless fuel	: 72.4%



The Bohemia X40 Inset has the same frontal appearance as the rest of the Bohemia family but can be installed directly into a standard  $16" \times 22"$  tapered fireback where an open fire was previously used. It can be fitted with or without a flue liner. Easy installation and improved fireplace efficiency can be achieved with the use of this stove.

Dimensions	: W545 x D342 x H606mm			
Dimensions for fireback	: W381 (tapering to 254) x D220 x H535mm			
Weight	: 55kg			
Max log length	: 300mm (12")			
Flue outlet	: 125mm top			
Efficiency wood	: 78.2%			
Efficiency smokeless fuel : 78.9%				







: W495 x D266 x H537mm
: 66kg
: 400mm (16")
: 125mm top/rear
: 79.5%
: 72.4%
: W495 X D266 X H200mm &

# 💥 40 CUBE & CUBE PANORAMA

4-5 kW Multi Fuel Stove

The popular Bohemia **X** 40 CUBE is now joined by its larger brother the **X** 60 CUBE, ideal when a larger heat output of up to 8kW is required. A fantastic full width door on both models gives an uninterrupted view of the fire burning brightly through the large window and for 2014 the brand new side window Panoramic models are introduced. The Panorama models offer an unrivalled view of the fire burning beautifully in the clean burn fire chamber from all directions. The Cube range offers sharp and contemporary clean lined styling making these stoves ideal when a minimalist and modern look is required. With a very wide firebox, it is possible to load a 16" length log or smokeless fuel and these stoves will give lovely warm and controllable radiant and convected heat. An optional H200mm or H400mm bolt-on logstore is available for both models.



Bohemia X40 Cube Panorama on 400mm height logstore

H400mm



# 6-8 kW Multi Fuel Stove

Dimensions	: W495 x D375 x H537mm
Weight of stove	:77kg
Max log length	: 400mm (16")
Flue outlet	: 125mm top/rear
Efficiency wood	: 80.4%
Efficiency smokeless fuel	: 71%
Logstore	: W495 X D352 X H200mm & H400mm



Bohemia X60 Cube Panorama





The Bohemia X50 is the most popular stove in the range and will suit the majority of fireplaces and room sizes. It has a deeper firebox than the X40 and will give greater output but with the same control and operation. With its clean burn technology the X50 is fully approved for use in smokeless zones throughout all areas of the UK.

Dimensions

Flue outlet

Max log length

Weight

- : W545 x D332.5 x H606mm : 72kg
- : 400mm (16")
- : 125mm top/rear

: 75.5% Efficiency wood Efficiency smokeless fuel : 70.2%





The Bohemia X60 is the largest stove in the range suitable for rooms where a greater heat output is required. A full sized firebox allows a large quantity of wood or smokeless fuel to be loaded. Easy and simple to operate with clean burn performance the X60 is fully approved for use in smokeless zones throughout all areas of the UK.

Dimensions Weight Max log length Flue outlet Efficiency wood

: W545 x D387.5 x H606mm

: 83kg

: 400mm (16") : 125mm top/rear

: 80.4%

Efficiency smokeless fuel : 71%

EXEMPTIO APPROVED



# TECHNICAL SPECIFICATIONS

Model:   30   40   voltest   voltest </th <th>TECHN</th> <th>ICAL SPECIFICATIONS</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>	TECHN	ICAL SPECIFICATIONS							
Height 521 606 606 537 606 607 606 607 606 607 606 607 537 606 607 332.5 387.5 375   Depth 290 292.5 342 266 332.5 387.5 375   Log Length 300 400 300 400 400 400 400   Nominal output KW 3.4 4.5 4.5 5.6 6.8 6.8   125mm Flue Outlet (T=Top R=Rear) T R T R T R T R T R T R T R 126 126 105 124 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126	X	Model:	30	40	40 Inset		50	60	
Depth 290 292.5 342 966 332.5 387.5 375   Weight in kg Weight with cast door 300 400 300 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400<		Width	390	545	545	495	545	545	495
Weight in kg Weight with cast door 51 58 66 72 55 61 60 72 78 83 89 77   Log Length 300 400 300 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 400 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126 126		Height	521	606	606	537	606	606	537
Log Length 300 400 300 400 400 400 400 400   Nominal output kW 3 4 4.5 4.5 4 5 6.8 6.8   125mm Flue Outlet (T=Top R=Rear) T R T R T R T R T R T R T R 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 12.6 1		Depth	290	292.5	342	266	332.5	387.5	375
Nominal output kW Range rating kW   3 3.4   4 4.5   4.5   4 4.5   4.5   5.6   6.8   6.8     125mm Flue Outlet (T=Top R=Rear)   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R   T R <th></th> <th>Weight in kg Weight with cast door</th> <th>51 <mark>58</mark></th> <th>66 72</th> <th>55 <mark>6</mark>1</th> <th>66</th> <th>72 <mark>78</mark></th> <th>83 <mark>89</mark></th> <th>77</th>		Weight in kg Weight with cast door	51 <mark>58</mark>	66 72	55 <mark>6</mark> 1	66	72 <mark>78</mark>	83 <mark>89</mark>	77
Range rating kW 3.4 4.5 4.5 5.6 6.8 6.8   125mm Flue Outlet (T=Top R=Rear) T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R <t< th=""><th></th><th>• •</th><th>300</th><th>400</th><th>300</th><th>400</th><th>400</th><th>400</th><th>400</th></t<>		• •	300	400	300	400	400	400	400
125mm Flue Outlet (T=Top R=Rear) T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R T R		-	3	4	4.5	4	5	6	6
Distance from rear of stove to centre of top flue outlet126126105124126126126Distance from floor to centre of rear flue outlet438520N/A449520520449Distance to flammable materials: From back From side From front From top250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250		Range rating kW	3-4	4-5	4-5	4-5	5-6	6-8	6-8
to centre of top flue outlet126126105124126126126Distance from floor to centre of rear flue outlet438520N/A449520520449Distance to flammable materials: From back From side From front From top250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250250<		125mm Flue Outlet (T=Top R=Rear)	TR	TR	Т	TR	TR	TR	TR
Distance from floor to centre of rear flue outlet 438 520 N/A 449 520 520 449   Distance to flammable materials: From back 250 250 250 250 250 250 449   Distance to flammable materials: From back 250 250 250 250 250 250 250 250 250 449   Distance to flammable materials: From back 250 250 250 250 250 250 250 250 250 449   Distance to flammable materials: From back 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 250 </th <th></th> <th>Distance from rear of stove</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>		Distance from rear of stove							
centre of rear flue outlet438520N/A449520520449Distance to flammable materials: From back From side From front From top250250200400,500250400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500400,500<		to centre of top flue outlet	126	126	105	124	126	126	126
Note   Note <th< th=""><th></th><th>Distance from floor to</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></th<>		Distance from floor to							
From back From side From front From top250250250250250250250Heating area in square metres20-8020-9020-9020-9020-9030-12030-14030-140Efficiency: Wood CO%: Wood CO%: Smokeless Fuel Decorative Cast Door Log Store Stand: 200mm height79.5779.58 72.4879.58 72.4879.58 72.4879.58 72.4879.58 72.4879.58 72.4870.28 71.4080.48% 71.4080.48% 71.40		centre of rear flue outlet	438	520	N/A	449	520	520	449
From side From front From top 400 400 200 400/500 400 400 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 800 8									
From front From top 800 275 801 275 801 <b< th=""><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></b<>									
From top 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 275 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140 30-140									
Heating area in square metres20-8020-9020-9030-12030-14030-140Efficiency: Wood Efficiency: Smokeless Fuel79.2% 0.15 0.15 0.2879.5% 0.14 0.1979.5% 0.74 0.1479.5% 0.14 0.1479.5% 0.14 0.15 0.3379.5% 0.14 0.15 0.3380.4% 0.15 0.14 0.15 0.17 0.1980.4% 0.15 0.14 0.15 0.1980.4% 0.15 0.14 0.15 0.1980.4% 0.15 0.14 0.15 0.1480.4% 0.15 0.14 0.1580.4% 0.15 0.14 0.15 0.1980.4% 0.15 0.14 0.1580.4% 0.14 0.15 0.15 0.17 0.1980.4% 0.15 0.14 0.1580.4% 0.14 0.15 0.15 0.1680.4% 0.15 0.14 0.1580.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.17 0.1980.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.17 0.1980.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.15 0.1680.4% 0.1680.4% 0.15 0.17 0.1980.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% 0.1680.4% <b< th=""><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></b<>									
Efficiency: Wood 79.2% 79.5% 78.2% 79.5% 75.5% 80.4% 80.4%   Efficiency: Smokeless Fuel 75% 72.4% 78.9% 72.4% 70.2% 71% 71%   CO%: Wood 0.15 0.14 0.14 0.14 0.14 0.14 0.15 0.17 0.17 0.17   CO%: Smokeless Fuel 0.28 0.33 0.19 0.33 0.4 0.15 0.17 0.19 0.19 0.15 0.19 0.19 0.19 0.15 0.17 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 <		From top	275	275	275	275	275	275	275
Efficiency: Smokeless Fuel 75% 72.4% 78.9% 72.4% 70.2% 71% 71% 0.17 0.17 0.17 0.17 0.19 0.19 0.33 0.14 0.19 0.33 0.15 0.17 0.19 0.19 0.15 0.19 0.19 0.19 0.15 0.17 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19 0.19		Heating area in square metres	20-80	20-90	20-90	20-90	30-120	30-140	30-140
CO%: Wood CO%: Smokeless Fuel 0.15 0.28 0.14 0.33 0.74 0.19 0.14 0.33 0.15 0.33 0.17 0.19 0.17 0.19   OPTIONS Vooden Handle Decorative Cast Door Log Store Stand: 200mm height Image: Comparison of the second secon		Efficiency: Wood	79.2%	79.5%	78.2%	79.5%	75.5%	80.4%	80.4%
CO%: Smokeless Fuel 0.28 0.33 0.19 0.33 0.33 0.19 0.19   OPTIONS Vooden Handle Image: Comparison of the comparison of th		Efficiency: Smokeless Fuel	75%	72.4%	78.9%	72.4%	70.2%	71%	71%
OPTIONS Image: Mooden Handle Image: Moode		CO%: Wood	0.15	0.14	0.74	0.14	0.15	0.17	0.17
Wooden HandleImage: Ample of the systemImage: Ample		CO%: Smokeless Fuel	0.28	0.33	0.19	0.33	0.33	0.19	0.19
Decorative Cast DoorImage: Image:	OPTIC	ONS							
Log Store Stand: 200mm height		Wooden Handle	1	$\checkmark$		1	1	-	1
		Decorative Cast Door	$\checkmark$	$\checkmark$	$\checkmark$		$\checkmark$	$\checkmark$	
		•				1			5

All stoves certified to: (€ EN13240 and EN13229 for Inset and all approved for smoke control areas



Wooden handle



Cast iron door

A twin baffle system increases the flame path, improving the efficiency and extracting further heat energy before the combustion gases leave the stove

> Tertiary air enters at the rear of firebox which mixes with the gases generated during the burning process burning off further hydrocarbons

Secondary air enters through the top air slider above the door, into the firebox, fuelling the fire and acting as an airwash to keep the glass clean

A fully Vermiculite lined fire chamber ensures a lovely flame pattern, high temperatures, greater efficiency and lower CO.

Primary air enters through the lower adjustable air slider and under the grate



Adjustable feet ensure the stove can always be levelled on uneven hearths

T









Bohemia **X40 CUBE PANORAMA** with Logstore



PEVEXCELLENCE!

Pevex Enterprises Limited T : 0044 (0)1473 736399 F : 0044 (0)1473 736406 E : sales@pevexenterprises.co.uk W: www.woodstoves.co.uk



Bohemia 💥 40 CUBE