



HETA
ECODESIGN READY

HETA TEST DATA FIGURES FOR ECODESIGN

	PARAMETERS				
	Efficiency in %	PM in mg/Nm ³	CO in mg/Nm ³	NoX in mg/Nm ³	CxHy OGC in mg/Nm ³
Requirement for Ecodesign	>75%	<40	<1500	<200	<120
Inspire 40/H	81%	27	1049	90	112
Inspire 45/H	84%	13	1052	112	74
Inspire 55/55H	80%	28	1250	130	100
Ambition 5	85%	22	1110	93	62
Ambition 8	80%	27	968	98	92
SL 7 series	83%	20	1125	74	81
SL 8 Series	81%	less than 3	657	99	32
Classic 1, Classic 2	81	29	678	99	48
SL 500/10,20,30 and Tour	83%	22	493	90	51
550 Inset	81.7	26	1000	87	56
Oura with with and without S/W	80%	11	1060	95	84
Solid C	79%	27	1063	109	81
Prestige Inset	79%	27	1063	109	81
Panoram XL / SL 100	81%	12	1244	95	100
Panorama / SL 95	80%	28	1121	106	46
SL 1000	86%	10	960	80	76
Kosi 6304	82%	17	1061	91	102
SL 800 series and SL 80 series	81%	30	650	82	51
SL 800 series with S/W	80%	8	824	101	50
SL 800 aqua	87%	22	666	115	48
SL 500 series, Napoli and Turin	81%	19	1162	82	41
SL 10, 20, 30, 40, 50, Tour	81%	19	1000	82	69